

# WB



## Weighing Balance

### Features:

- 1) 1/30,000 and 1/60,000 display resolution available
- 2) Auto calibration
- 3) Weighing, counting and percentage modes
- 4) Setting the usable units from 13 weighing units
- 5) High resolution switch function to display 10 times
- 6) Divisions (approved model only)
- 7) Default unit selectable; auto-off timer setting
- 8) Backlight mode setting; digital filter setting; adjustable
- 9) Gravity value and external weight calibration
- 10) 1/15,000 non-linearity for 1/30,000 model and 1/30,000
- 11) Non-linearity for 1/50,000 and 1/60,000 model
- 12) Full duplex RS-232 interface and wind shield included
- 13) Low power indication, time indication, and auto power off
- 14) Easily adjusted leveling feet for stability of the scale

### Options:

- 1) RTC card
- 2) 6V/1.2Ah rechargeable battery

### Specifications

Model	Capacity	Accuracy Resolution
WB-150	150 g 0.005g	1/30,000
WB-300	300 g 0.01g	1/30,000
WB-600	600 g 0.02g	1/30,000
WB-1200	1200 g 0.02g	1/60,000
WB-1500	1500 g 0.05g	1/30,000
WB-3000	3000 g 0.1g	1/30,000

**Pan Size** (W\*D): capacity < 1200g,  $\Phi$ 120mm (round) capacity > 1200g, 151\*126\*6.5mm (square)

Dimension(W\*D\*H): 184\*264\*75mm

Display : LCD, 6 1/2 digits, 16 mm (Height), LED backlight

Maximum Humidity: 85% relative humidity

### Power Supply:

- 1)DC 9V adaptor
- 2) 4UM-2 1.5V dry batteries (not included) or 6V/1.2AH rechargeable battery (optional)

**Operation** Temperature: 5°C ~ 35°C (41°F ~ 95°F)