

JIK Weighing Indicator



■ Features

- Easy to read large LCD display with green LED backlight
- Both stainless steel and ABS structure are available
- Dual channel as a standard feature for JIK-8 (connection to larger platforms and floor scales)
- Zero / Tare / Weighing / Simple counting / Percent weighing / Net / Gross / Accumulation / Serial No. / Check weighing functions
- Auto shut off for power saving
- Options: 2 Relay interfaces, 1 RS-232 interface
- JIK indicator is the solution to your weighing indicator applications that require multiple functions, rugged construction, comprehensive yet intuitive software and multiple connectively options

■ Specifications

Model	JIK-6 CAB	JIK-6 CSB	JIK-8 CAB	JIK-8 CSB
Housing	ABS	Stainless steel	ABS	Stainless steel
Resolution	1/30000		1/60000	
Weighing units	kg / g / lb / pcs / %			
Display	6 digits, 30mm digit height, green backlit LCD display			
Dimension(mm)	250×150×90			
Weight(kg)	Net weight: 2.5 Gross weight: 2.93	Net weight: 3.03 Gross weight: 3.46	Net weight: 2.5 Gross weight: 2.93	Net weight: 3.03 Gross weight: 3.46
Power supply	9V/ 1A adaptor, or 6V/3Ah rechargeable battery			
Load cell excitation	DC 5V, Up to 8x350 ohm load cells			
Operating Temp	-5 ~ 40°C			
Certification	OIML , CE			

The specifications and external design are subject to change without notice for further improvement

JADEVER
MORE THAN WEIGHING



Jadever Scale Co., Ltd.

Tel:+886-2-22990203 Fax:+886-2-22990204
<http://www.jadever.com> E-mail:sales@jadever.com.tw

Xiamen Jadever Co., Ltd.

Tel:+86-592-6037668 Fax:+86-592-6037028
<http://www.jadever.com> E-mail:jadever@jadever.com.cn
xmjadever@jadever.com.cn

Jadever Weightech, Inc.

Tel:+1-905-482-2618 Fax:+1-905-887-4066
<http://www.jadeverscale.com> E-mail:james@jadeverscale.com