

# JLT Crane Scale



## ■ Features

- Special design, quick to show exact weight
- 360° freely swiveling hook
- Extra bright red LED, easy to read
- Battery life 150 hours
- Recharging time 8 hours
- Overload safety: 200% of rated capacity
- Ultimate overload: 400% of rated capacity
- Auto Calibration
- Optional accessory: wireless remote controller
- With HOLD/TARE/ZERO function
- Two selectable resolution for each model
- Options: remove control, heat insulation board, AC-01N handheld RF weighing indicator and RS-232 interface
- Rugged and reliable construction, suitable for all kinds of heavy-duty measurements

## ■ Specifications

Model	JLT -600	JLT -1T	JLT -2T	JLT -3T	JLT -5T	JLT -7.5T	JLT -10T	JLT -15T	JLT -20T	JLT -25T	JLT -30T	JLT -35T
Capacity(kg)	600	1000	2000	3000	5000	7500	10000	15000	20000	25000	30000	35000
Division(kg)	0.2	0.5	1	1	2	5	5	10	10	10	10	10
Net weight(kg)	12.0	12.2	12.5	12.5	21.0	26.3	35.0	42.0	78.0	78.0	119.0	119.0
Display	5 digits, 25mm digit height, red backlit LED display											
Power supply	6 V/ 10 Ah rechargeable battery or 12V/1A via main adapter											
Operating Temp	-25°C ~ +55°C											
Certification	CE											

The specifications and external design are subject to change without notice for further improvement

**JADEVER**  
MORE THAN WEIGHING



### Jadever Scale Co., Ltd.

Tel: +886-2-22990203 Fax: +886-2-22990204  
http://www.jadever.com E-mail: sales@jadever.com.tw

### Xiamen Jadever Co., Ltd.

Tel: +86-592-6037668 Fax: +86-592-6037028  
http://www.jadever.com E-mail: jadever@jadever.com.cn  
xmjadever@jadever.com.cn

### Jadever Weigtech, Inc.

Tel: +1-905-482-2618 Fax: +1-905-887-4066  
http://www.jadeverscale.com E-mail: james@jadeverscale.com